



SteelROCK
PACIFIC VILLA-TILE™

Your permanent solution!

Combining the strength of today's high yield Galvalume® steel with the most popular tile design on the market, Pacific Villa-Tile offers the best protection for your home - without sacrificing beauty. And at only 1.5 lbs. per square foot, Pacific Villa-Tile is one of the lightest roofing tiles available which means you can enjoy the durability of a tile roof without the worry of excessive weight.

Whether you need a new roof or a replacement roof, SteelROCK's Pacific Villa-Tile's angular design and graceful slopes create a rich, deep profile that is suitable for numerous architectural styles and complies with most homeowner's association guidelines.

The Pacific Villa-Tile design helps protect your home from fire, high winds, hail and snow by coupling steel and rock into a single shield against the elements. And Pacific Villa-Tile's solid construction makes it the permanent solution for your home.

– SteelROCK PACIFIC VILLA-TILE



SteelROCK
ROOF PRODUCTS



Strong | Durable | Timeless

Every panel is formed from 26-gauge Galvalume® steel and covered with natural rock granules that are embedded in a 100% acrylic resin basecoat. The panels are then finished with a clear acrylic overglaze.

SteelROCK panels are durable, lightweight and have surpassed the industry's highest performance tests to date. All SteelROCK stone-coated *blended colors are enhanced with flashes of rock granules in either a dark or light accent to add a subtle beauty to the roof's overall appearance.

The panels are backed by a Class-4 Hail impact (UL 2218) resistance rating and a Lifetime* limited warranty covering 120-mph winds. SteelROCK is proud to offer today's homeowners and builders a material that will provide years of maintenance free protection.

- **Lifetime Limited Warranty**

(Non-prorated & fully transferable, *residential single family dwellings, not applicable to entities capable of an infinite life.)

- **Walkable**

(26-ga., Galvalume® Steel)

- **Lightweight**

(1.5 lbs / per sq. ft.)

- **Class-A Fire Rated**

(Verify correct underlay to meet codes)

- **120-mph Wind Warranty**

(Tested in the harshest conditions, can be engineered to meet FL HVHZ wind codes 150-mph)

- **Hail Impact Warranty**

(No perforation of the SteelROCK panel from hail UL 2218 Class-4 rated)

Panel Coating Layers



Barcelona

Dark Accent

Mission Gold

Dark Accent

Mission Red

Solid Color

Terra-Cotta

Light Accent

Always select colors from ACTUAL samples. STANDARD colors are shown above. Custom colors and Flashing are available.

* Solid colors CHARCOAL, MISSION RED, PEARL WHITE etc. do not receive a flash accent.

SteelROCK

ROOF PRODUCTS

2438 East Chapman Ave. Suite 24
Fullerton, CA, USA 92870
Toll Free: 1(800) 987-3199
fax: (951)-245-1156
Email: info@steelrockroof.com
www.steelrockroof.com

TESTING CREDENTIALS

ICC Evaluation Report #5218

*Galvalume® is a registered trademark of BIEC International
SteelROCK ©2006. SteelROCK Roof Products. Printed in the U.S.A.